

Gate Valve, 2" - 2½" Dissectible



Model: 251K

Valves are critical parts of many different types of equipment found throughout industry. For example, gate valves, often called sluice valves, are valves that open by lifting a barrier out of the path of a fluid.

Gate valves are widely used for a variety of applications, such as pipelines. Suitable for both above-ground and underground applications, gate valves are designed for fully-open or fully-closed service and should not be used as control or regulator valves.

Industrial maintenance technicians need a solid understanding of how to operate, construct, and maintain a wide variety of different types of valves, including industrial gate valves. DAC Worldwide's Gate Valve, 2" - 2½" Dissectible (251K) is actual industrial hardware, sourced from common gate valve makes and models.

Industry-Standard Components Provide Realistic, Hands-On Training

Technical training is most effective when learners can gain hands-on practice with industry-standard components they'll encounter on the job. The Gate Valve Dissectible features a common, industrial-quality gate valve that will provide learners with a realistic training experience to build skills that translate easily to the workplace.

The Gate Valve Dissectible consists of an actual industrial gate valve that industrial maintenance technicians will commonly encounter on the job. This industry-standard gate valve is mounted onto a welded-steel stand for easy access.

This Dissectible allows students to disassemble and reassemble a gate valve in order to build competency in understanding how the valve works, the basic components, and routine maintenance.

FEATURES & SPECIFICATIONS

- Cleaning, priming, and painting using a high-durability, urethane coating.
- Replacement, plated hardware where required.
- Welded, formed-steel mounting stand with provision for tabletop mounting.
- Provision for mounting on related bench, workstation, and storage rack products.
- Packaging for shipment via motor freight or parcel service.

PRODUCT DIMENSIONS

DISCLAIMER: Product Dimensions are approximate. Shipping Dimensions and Weights are for directional use only and may change based on manufacturer variables. For the most accurate Shipping Dimensions and Weights, please contact the manufacturer.

- **Product Dimensions**
Weight Varies: 35-40 lbs. (16-20kg) each.
- **Shipping Dimensions**
Shipping Weight Varies: 65-85 lbs. (29-39 kg) each.

OPTIONS

- Recommended #902V - Mobile Display Stand
- #530-000 - Pipe Trades Manual (IPT)
- #530-001 - Pipe Trades Handbook (IPT)

Address

DAC Worldwide

Contacts

email: dacwcontact@amatrol.com

3 Killdeer Court, Suite #301
Swedesboro, NJ 08085

phone: (800) 662 5877